

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 03/06/2014 Date of issue: 03/06/2014

Version: 1.0

### **SECTION 1: IDENTIFICATION**

### 1.1. Product Identifier

Product Name: Premium Dish Plus

1.2. Intended Use of the Product

Use of the substance/mixture: Detergent for Commercial Dish Machines. For professional use only.

### 1.3. Name, Address, and Telephone of the Responsible Party

### Company

Atlanta Super Source, Inc. 3655 Kennesaw Á 5 Á Parkway, Á Suite Á 100 Kennesaw, GA 30144 770-423-0006

### 1.4. Emergency Telephone Number

Emergency Number : 800-424-9300 CHEMTREC

# **SECTION 2: HAZARDS IDENTIFICATION**

### 2.1. Classification of the Substance or Mixture

# Classification (GHS-US)

Met. Corr. 1 H290 Acute Tox. 4 (Oral) H302 Skin Corr. 1A H314 Eye Dam. 1 H318

#### 2.2. Label Elements

#### **GHS-US Labeling**

Hazard Pictograms (GHS-US)





Signal Word (GHS-US) : Danger

Hazard Statements (GHS-US) : H290 - May be corrosive to metals

H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

**Precautionary Statements (GHS-US)** : P234 - Keep only in original container.

P260 - Do not breathe vapors, spray, mist.

P264 - Wash hands, forearms, and exposed areas thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P280 - Wear eye protection, protective gloves, protective clothing. P301+P312+P330+P331 - IF SWALLOWED: Call a POISON CENTER or

doctor/physician if you feel unwell. Rinse mouth. Do NOT induce vomiting. P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all

contaminated clothing. Rinse skin with water/shower.

 $\mbox{P304+P340}$  - IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER or doctor/physician.

P321 - Specific treatment (see Section 4).

P363 - Wash contaminated clothing before reuse.

P390+P391 - Absorb spillage to prevent material damage. Collect spillage.

P405 - Store locked up.

P406 - Store in corrosive resistant container with a resistant inner liner.

P501 - Dispose of contents/container to local, regional, national, and international

regulations.

03/06/2014 EN (English US) 1/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 2.3. Other Hazards

Other Hazards Not Contributing to the Classification: Corrosive to the respiratory tract.

Aquatic Acute 1

Aquatic Chronic 2

H400 - Very toxic to aquatic life

H411 - Toxic to aquatic life with long lasting effects

P273 - Avoid release to the environment

# 2.4. Unknown Acute Toxicity (GHS-US)

No data available



# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1. Substance

Not applicable

## 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Potassium hydroxide	(CAS No) 1310-58-3	29.87	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Eye Dam. 1, H318
Sodium hypochlorite	(CAS No) 7681-52-9	4.4805	Met. Corr. 1, H290 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Potassium carbonate	(CAS No) 584-08-7	2.49	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Potassium silicate	(CAS No) 1312-76-1	1.46	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 STOT SE 3, H335

Full text of H-phrases: see section 16

# **SECTION 4: FIRST AID MEASURES**

## 4.1. Description of First Aid Measures

**First-aid Measures General**: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice. **First-aid Measures After Inhalation**: If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

**First-aid Measures After Skin Contact**: Remove contaminated clothing. Immediately flush skin with plenty of water for at least 60 minutes. Immediately call a POISON CENTER or doctor/physician.

**First-aid Measures After Eye Contact**: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 60 minutes. Immediately call a POISON CENTER or doctor/physician.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor.

# 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms/Injuries:** Corrosive to eyes, respiratory system and skin. Harmful if swallowed.

Symptoms/Injuries After Inhalation: Corrosive to the respiratory tract.

Symptoms/Injuries After Skin Contact: Corrosive. Causes burns.

Symptoms/Injuries After Eye Contact: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Harmful if swallowed.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

# **SECTION 5: FIRE-FIGHTING MEASURES**

# 5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

03/06/2014 EN (English US) 2/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

**Explosion Hazard:** Product is not explosive.

**Reactivity:** The substance decomposes on heating, on contact with acids and under influence of light producing toxic and corrosive gases including chlorine. The substance is a strong oxidant and reacts with combustible and reducing materials.

### 5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Do not allow run-off from fire fighting to enter drains or water courses.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not allow contact with metals. Do not get in eyes, on skin, on clothing. Do not breathe vapor, mist, gas.

#### 6.1.1. For Non-emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

### 6.1.2. For Emergency Responders

**Protective Equipment:** Equip cleanup crew with proper protection. **Emergency Procedures:** Ventilate area. Stop leak if safe to do so.

## 6.2. Environmental Precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and Material for Containment and Cleaning Up

**For Containment:** Cautiously neutralize spilled liquid. Absorb/contain spill with inert material, then place in suitable container. **Methods for Cleaning Up:** Clear up spills immediately and dispose of waste safely.

### 6.4. Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

# **SECTION 7: HANDLING AND STORAGE**

# 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** Ammonium or nitrogen containing compounds can react with the sodium hypochlorite in this product releasing toxic chlorine gas.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

# 7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Storage areas should be periodically checked for corrosion and integrity.

Incompatible Products: Metals. Ammonia. Reducing agents. Combustible materials. Strong acids.

Special Rules on Packaging: Store in original container or corrosive resistant and/or lined container.

7.3. Specific End Use(s) Detergent for Commercial Dish Machines. For professional use only.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1. Control Parameters

Sodium hydroxide (1310-73-2)		
USA ACGIH	ACGIH Ceiling (mg/m³)	2 mg/m³
<b>USA NIOSH</b>	NIOSH REL (ceiling) (mg/m³)	2 mg/m³
USA IDLH	US IDLH (mg/m³)	10 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	2 mg/m³
Potassium hydroxide (1310-58-3)		
USA ACGIH	ACGIH Ceiling (mg/m³)	2 mg/m³
USA NIOSH	NIOSH REL (ceiling) (mg/m³)	2 mg/m³

# 8.2. Exposure Controls

**Appropriate Engineering Controls** 

: Ensure all national/local regulations are observed. Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

03/06/2014 EN (English US) 3/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Personal Protective Equipment** : Protective clothing. Safety glasses. Face shield. Gloves. Insufficient ventilation: wear

respiratory protection.











Materials for Protective Clothing : Corrosionproof clothing.

**Hand Protection** : Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or face shield.Skin and Body Protection: Wear suitable protective clothing.

**Respiratory Protection** : Use a NIOSH-approved respirator or self-contained breathing apparatus whenever

exposure may exceed established Occupational Exposure Limits.

**Other Information** : When using, do not eat, drink or smoke.

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

# 9.1. Information on Basic Physical and Chemical Properties

Physical State : Liquid

**Appearance** : Yellowish, translucent

Odor : Slight Chlorine
Odor Threshold : No data available

pH : 14

Relative Evaporation Rate (butylacetate=1): No data availableMelting Point: No data availableFreezing Point: No data availableBoiling Point: 100 (212 °F)

Flash Point : None

**Auto-ignition Temperature** : No data available **Decomposition Temperature** : No data available Flammability (solid, gas) : No data available **Vapor Pressure** : No data available Relative Vapor Density at 20 °C : No data available **Relative Density** : 1.21 (water = 1) Solubility Complete. Partition coefficient: n-octanol/water : No data available

Viscosity : No data available

**9.2.** Other Information No additional information available

# **SECTION 10: STABILITY AND REACTIVITY**

- **10.1 Reactivity:** The substance decomposes on heating, on contact with acids and under influence of light producing toxic and corrosive gases including chlorine. The substance is a strong oxidant and reacts with combustible and reducing materials.
- **10.2** Chemical Stability: Stable under recommended handling and storage conditions (see section 7).
- 10.3 Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
- **10.4 Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Contact with metallic substances.
- 10.5 Incompatible Materials: Strong acids. Metals. Reducing agents. Combustible materials. Ammonia.
- **10.6** Hazardous Decomposition Products: Carbon oxides (CO, CO<sub>2</sub>). Chlorine gas. Sodium oxides. Potassium oxides.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

### 11.1. Information On Toxicological Effects

Acute Toxicity: Harmful if swallowed.

Sodium hypochlorite (7681-52-9)	
LD50 Oral Rat	8200 mg/kg
LD50 Dermal Rabbit	> 10000 mg/kg
Potassium silicate (1312-76-1)	
LD50 Oral Rat	1300 mg/kg

03/06/2014 EN (English US) 4/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Potassium hydroxide (1310-58-3)	
LD50 Oral Rat	214 mg/kg
ATE (Oral)	333.000 mg/kg body weight
Potassium carbonate (584-08-7)	
LD50 Oral Rat	1870 mg/kg

Skin Corrosion/Irritation: Causes severe skin burns and eye damage. (pH: 14)

Serious Eye Damage/Irritation: Causes serious eye damage. (pH: 14)

Respiratory or Skin Sensitization: Not classified

**Germ Cell Mutagenicity:** Not classified **Carcinogenicity:** Not classified

Sodium hypochlorite (7681-52-9)	
IARC group	3

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

**Symptoms/Injuries After Inhalation:** Corrosive to the respiratory tract.

Symptoms/Injuries After Skin Contact: Corrosive. Causes burns.
Symptoms/Injuries After Eye Contact: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Harmful if swallowed.

# **SECTION 12: ECOLOGICAL INFORMATION**

### 12.1. Toxicity

**Ecology - General** : Toxic to aquatic life with long lasting effects.

Sodium hypochlorite (7681-52-9)		
LC50 Fish 1	0.06 (0.06 - 0.11) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
EC50 Daphnia 1	0.033 - 0.044 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	
LC 50 Fish 2	4.5 (4.5 - 7.6) mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 Daphnia 2	0.033 (0.033 - 0.044) mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	
Potassium silicate (1312-76-1)		
LC50 Fish 1	301 - 478 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)	
LC 50 Fish 2	3185 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])	

# 12.2. Persistence and Degradability No additional information available

### 12.3. Bioaccumulative Potential

Potassium silicate (1312-76-1)		
BCF fish 1	(no bioaccumulation expected)	
Potassium hydroxide (1310-58-3)		
Log Pow	0.65	

- 12.4. Mobility in Soil No additional information available
- 12.5. Other Adverse Effects No additional information available

# **SECTION 13: DISPOSAL CONSIDERATIONS**

# 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, and international regulations. RCRA Waste Code: D002 (Corrosive Material).

# **SECTION 14: TRANSPORT INFORMATION**

In Accordance With ICAO/IATA/IMDG/DOT

14.1. UN Number

**DOT NA no.** : NA1760

14.2. UN Proper Shipping Name

**DOT Proper Shipping Name** : Compounds, cleaning liquid

**Department of Transportation (DOT)** : 8 - Class 8 - Corrosive material 49 CFR 173.136

**Hazard Classes** 

03/06/2014 EN (English US) 5/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Hazard Labels (DOT)** 

: 8 - Corrosive



**DOT Symbols** : D - Proper shipping name for domestic use only, G - Identifies PSN requiring a

technical name

**DOT Special Provisions (49 CFR 172.102)** : B2 - MC 300, MC 301, MC 302

: B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

N37 - This material may be shipped in an integrally-lined fiber drum (1G) which meets the general packaging requirements of subpart B of part 173 of this subchapter, the requirements of part 178 of this subchapter at the packing group assigned for the material and to any other special provisions of column 7 of the 172.101 table.

T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 95 / (1 + a (tr - tf)) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: a = (d15 - d50) / 35d50 Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at d50 (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx)

: 202 : 242

154

Marine pollutant : Yes



### 14.3. Additional Information

**Emergency Response Guide (ERG) Number** 

**Transport by Sea** 

**DOT Vessel Stowage Location** 

: 154

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers

specified in paragraph (k)(2)(i) of this section is exceeded.

**DOT Vessel Stowage Other** 

**Air Transport** 

: 40 - Stow "clear of living quarters"

DOT Quantity Limitations Passenger Aircraft/Rail (49 CFR 173.27) : 1 L
DOT Quantity Limitations Cargo Aircraft Only (49 CFR 175.75) : 30 L

03/06/2014 EN (English US) 6/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# **SECTION 15: REGULATORY INFORMATION**

### 15.1 US Federal Regulations

Premium Dish Plus	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
	Reactive hazard

### Sodium hypochlorite (7681-52-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### Potassium silicate (1312-76-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Potassium hydroxide (1310-58-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Potassium carbonate (584-08-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

## 15.2 US State Regulations

# Sodium hypochlorite (7681-52-9)

- U.S. Delaware Pollutant Discharge Requirements Reportable Quantities
- U.S. Louisiana Reportable Quantity List for Pollutants
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 1 and 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1 and 2
- U.S. Massachusetts Right To Know List
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. Michigan Polluting Materials List
- U.S. Minnesota Hazardous Substance List
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Texas Effects Screening Levels Long Term and Short Term

### Potassium silicate (1312-76-1)

U.S. - Texas - Effects Screening Levels - Long Term

# Potassium hydroxide (1310-58-3)

- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- U.S. Delaware Pollutant Discharge Requirements Reportable Quantities
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Louisiana Reportable Quantity List for Pollutants
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 1 and 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1 and 2
- U.S. Massachusetts Right To Know List
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. Michigan Occupational Exposure Limits Ceilings
- U.S. Michigan Polluting Materials List
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits Ceilings
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances

03/06/2014 EN (English US) 7/8

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- U.S. North Dakota Air Pollutants Guideline Concentrations 1-Hour
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Tennessee Occupational Exposure Limits Ceilings
- U.S. Texas Effects Screening Levels Long Term and Short Term
- U.S. Vermont Permissible Exposure Limits Ceilings
- U.S. Washington Permissible Exposure Limits Ceilings
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 25 Feet to Less Than 40 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 40 Feet to Less Than 75 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 75 Feet or Greater
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights Less Than 25 Feet

### Potassium carbonate (584-08-7)

U.S. - Texas - Effects Screening Levels - Long Term and Short Term

# SECTION 16: OTHER INFORMATION, INCLUDING DATA ON DATE OF PREPARATION OR LAST REVISION

**Revision date** : 03/06/2014

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard

Communication Standard 29 CFR 1910.1200.

### **GHS Full Text Phrases:**

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H290	May be corrosive to metals
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)

03/06/2014 EN (English US) 8/8